



SHIVER 900 - TECHNICAL SPECIFICATIONS

ENGINE	Aprilia 90° V-Twin, 4-stroke, four valves per cylinder, liquid cooled. Ride-by-Wire system with 3 engine maps
DISPLACEMENT	896.1 cc
MAX. POWER AT CRANKSHAFT	95 HP (70 kW) at 8,750 rpm
MAX. TORQUE AT CRANKSHAFT	90 Nm at 6,500 rpm
FRONT SUSPENSION	Kayaba upside-down fork, Ø 41 mm stanchions adjustable in preload and hydraulic rebound damping Wheel travel: 120 mm
REAR SUSPENSION	Aluminium alloy swingarm Sachs monoshock absorber adjustable in preload and hydraulic rebound damping. Wheel travel: 130 mm
FRONT BRAKE	Ø 320 mm floating double disc with aluminium flange. Metal braid brake pipe. Radial callipers with four pistons. ABS Continental
REAR BRAKE	Ø 240 mm wave stainless steel disc. Single piston calliper Metal braid brake pipe. ABS Continental
FRONT WHEEL	3-spoke 3.5" x 17" aluminium alloy wheel. Tyre: 120/70 ZR 17"
REAR WHEEL	3-spoke 6" x 17" aluminium alloy wheel. Tyre: 180/55 ZR 17"
SADDLE HEIGHT	810 mm
FUEL TANK CAPACITY	15 lt
DRY WEIGHT	199 kg
WET WEIGHT	218 kg
EMISSIONS COMPLIANCE	Euro 4
EMISSIONS	123 g/km (CO ₂)
CONSUMPTION	5.31 l/100km
ELECTRONIC MANAGEMENT	Traction control, Aprilia Mia (multimedia platform), navigation system
COLOUR RANGE	Hi-Tech Silver, Challenging Red, Innovation Dark
ACCESSORIES	Windshield, led flasher, aluminium rear mirror, clutch and brake tank cap, central stand, Akrapovic homologated slip-on, semi-rigid pannier with mount kit